

SPECIFICATIONS

2015 VULCAN® 900 CUSTOM



POWER

Engine	Four-stroke, liquid-cooled, SOHC, four valves per cylinder V-twin
Displacement	903cc / 55.1 cu in
Bore x Stroke	88 x 74.2mm
Compression ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3,500 rpm
Fuel System	DFI® with dual 34mm Keihin throttle bodies
Ignition	TCBI with digital advance
Transmission	Five-speed with positive neutral finder
Final Drive	Belt

PERFORMANCE

Front Suspension / Wheel Travel	41mm hydraulic telescopic fork / 5.9 in
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload / 4.1 in
Front Tire	80/90x21
Rear Tire	180/70x15
Front Brakes	300mm hydraulic disc
Rear Brakes	270mm hydraulic disc
Cooling System	Liquid

DETAILS

Frame Type	Double cradle, high-tensile steel
Rake/Trail	33 degrees / 7.2 in
Overall Length	94.7 in
Overall Width	35.2 in
Overall Height	44.1 in
Ground Clearance	5.5 in
Seat Height	27.0 in
Curb Weight	610.8 lb**
Fuel Capacity	5.3 gal
Wheelbase	64.8 in
Color Choices	Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).