

SPECIFICATIONS

2015 NINJA[®] ZX™-10R ABS



POWER

Engine	Four-stroke, liquid-cooled, DOHC, four valves per cylinder, inline-four
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression ratio	13.0:1
Fuel System	DFI [®] with four 47mm Keihin throttle bodies with oval sub-throttles, two injectors per cylinder
Ignition	TCBI with digital advance and Sport-Kawasaki Traction Control (S-KTRC)
Transmission	Six-speed
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Big Piston Fork (BPF), adjustable stepless rebound and compression damping, spring preload adjustability / 4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload / 5.5 in
Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Kawasaki Intelligent anti-lock Braking (KIBS), dual semi-floating 310mm petal discs with dual four-piston radial-mounted calipers
Rear Brakes	KIBS-controlled, single 220mm petal disc with aluminum single-piston caliper
Cooling System	Liquid

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	25.0 degrees / 4.2 in
Overall Length	81.7 in
Overall Width	28.1 in
Overall Height	43.9 in
Ground Clearance	5.3 in
Seat Height	32.0 in
Curb Weight	443.2 lb**
Fuel Capacity	4.5 gal
Wheelbase	56.1 in
Color Choices	Metallic Matte Carbon Gray / Flat Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).