

SPECIFICATIONS

2015 NINJA® 1000 ABS



POWER

Engine	Four-stroke, liquid-cooled, DOHC, four valves per cylinder, inline-four
Displacement	1,043cc
Bore x Stroke	77.0 x 56.0 mm
Compression ratio	11.8:1
Fuel System	DFI® with four 38mm Keihin throttle bodies, oval sub-throttles
Ignition	TCBI with digital advance
Transmission	Six-speed
Final Drive	Sealed-ring chain

PERFORMANCE

Front Suspension / Wheel Travel	41mm inverted cartridge fork with stepless compression and rebound damping, adjustable spring preload / 4.7 in
Rear Suspension / Wheel Travel	Horizontal monoshock with stepless rebound damping, remotely adjustable spring preload / 5.4 in
Front Tire	120/70 ZR17
Rear Tire	190/50 ZR17
Front Brakes	Dual 300mm petal-type rotors with radial-mount four-piston monobloc calipers and ABS
Rear Brakes	Single 250mm petal-type rotor with single-piston caliper and ABS
Cooling System	Liquid

DETAILS

Frame Type	Aluminum backbone
Rake/Trail	24.5 degrees / 4.0 in
Overall Length	82.9 in
Overall Width	31.1 in
Overall Height	46.1 / 48.4 in (windscreen DN/UP)
Ground Clearance	5.3 in
Seat Height	32.3 in
Curb Weight	509.4 lb**
Fuel Capacity	5.0 gal
Wheelbase	56.9 in
Color Choices	Candy Lime Green / Metallic Spark Black, Metallic Carbon Gray / Metallic Spark Black
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, 48 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).